



DATA SHEET: TG40 SERIES LED ALUMINIUM FLOODLIGHTS



FEATURES

- PREWIRED 1M FLEX
- SLIM PROFILE
- IP65 RATED
- DIE CAST ALUMINIUM
- DUAL VOLTAGE
- EASY MOUNT BRACKET

CODE	Description	Wattage	Lumen	Colour Temp	Dimensions
TG40-50W	50W LED FLOODLIGHT	50W	4500	5000K	275x220x32
TG40-100W	100W LED FLOODLIGHT	100W	9000	5000K	345x280x57
TG40-150W	150W LED FLOODLIGHT	150W	13500	5000K	380x310x70
TG40-200W	200W LED FLOODLIGHT	200W	18000	5000K	418x350x80
TG40-300W	300W LED FLOODLIGHT	300W	27000	5000K	470x395x95
TG40-50W/2K	50W LED FLOODLIGHT	50W	4200	2000K	275x220x32
TG40-100W/2K	100W LED FLOODLIGHT	100W	8400	2000K	345x280x57
TG40-50W/2K/PC	50W LED FLOODLIGHT 2K, WITH PHOTOCELL	50W	4200	2000K	275x220x32
TG40-50W/5K/PC	50W LED FLOODLIGHT 5K, WITH PHOTOCELL	50W	4500	5000K	275x220x32
TG40-100W/2K/PC	100W LED FLOODLIGHT 2K, WITH PHOTOCELL	100W	8400	2000K	345x280x57
TG40-100W/5K/PC	100W LED FLOODLIGHT 5K, WITH PHOTOCELL	100W	9000	5000K	345x280x57

SPECIFICATION

- Finish: BLACK
- Dimmable: NO
- Cri: >80
- Rated Life Hrs: 25,000
- Voltage: 230/110V
- Material: ALUMINIUM